

TECHNICAL SPECIFICATIONS- EDOSE			
MECHANICAL	Dosing Capacity @ 4Kg/Cm <sup>2</sup>	LPH	6 & 10
	Max. Operating Pressure	Kg/Cm <sup>2</sup>	7
	Max. Stroke Frequency	strokes/min	400
ELECTRICAL	Voltage	V	230 (+/- 20%)
	Length of main cable	m	2
	Max. power consumption	W	30
	Electric safety class	-	2
	Pollution degree	-	3
	Ingress Protection	IP	65
SOUND	Max. sound pressure level	dB	< 60
MOC	Pump Head	PLASTICS	GF PP
	Diaphragm		PTFE
	Connectors		GF PP
	Suction/Discharge Tubing		PE
	Plunger	METALS	SS-304
	Copper		Class-H

Available with Your Trusted Partner for Water Treatment Solutions:

## FILTRA CONSULTANTS AND ENGINEERS LTD.

Gala No. 2 & 3, Ground Floor, Neminath Industrial Estate No. 2, Navghar, Vasai (East), Dist.: Palghar - 401 219  
 Tel.: +91 8691009127/26 Email: [filtraw@gmail.com](mailto:filtraw@gmail.com) Website: [www.ewatertreatmentindia.com](http://www.ewatertreatmentindia.com)

